

Broadcast FM transmitter mod. ESVA250



TECHNICAL FEATURES

FREQUENCY RANGE:	87.5÷108 MHz (76÷88 MHz on request)
MODULATION:	FM
EMISSION CLASS:	F3E
VCO TUNING:	25 MHz
FREQUENCY STABILITY:	± 2.5 ppm
SYNTHESIZER STEP:	10KHz
POWER OUTPUT:	0 ÷ 250 W (max.270W)
SPURIOUS EMISSION:	< -80 dB or better
HARMONIC EMISSION:	< -65 dB
STEREO SEPARATION:	> 55 dB @ 1KHz
DISTORSION:	< 0.1 % (TYP. 0.06%) @ 1KHz
BASE BAND:	30 Hz ÷ 60 KHz within 0.15 dB
UNWEIGHTED S/N RATIO:	> 80 dB (30Hz ÷ 15KHz 50 uS RMS)
ASYNCRONOUS AM S/N Ratio:	> 70 dB Ref. 100% AM 400Hz
SYNCRONOUS AM S/N Ratio:	> 65 dB with FM @ 75KHz @400Hz
PRE-ENPHASIS:	50 OR 75 μ s int. selectable
RF OUT CONNECTOR:	N-F 50 Ohm
MPX INPUT CONNECTOR:	BNC-F
MPX INPUT IMPEDANCE:	2 KOhm
SCA INPUT CONNECTOR:	3 BNC-F
COOLING:	Forced air by brushless fan
OP.TEMPERATURE RANGE:	- 10 ÷ +45 °C
MAXIMUM UMIDITY:	90 %
AC SUPPLY:	100 ÷ 240 VAC - 47 ÷ 63 Hz
DIMENSION:	2 unit rack 19", 435mm depth
WEIGHT:	12Kg